

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : G06F 9/54		A2	(11) International Publication Number: WO 00/65441 (43) International Publication Date: 2 November 2000 (02.11.00)
(21) International Application Number: PCT/US00/10426 (22) International Filing Date: 18 April 2000 (18.04.00) (30) Priority Data: 09/298,603 23 April 1999 (23.04.99) US (71) Applicant: ORACLE CORPORATION [US/US]; 500 Oracle Parkway, Redwood Shores, CA 94065 (US). (72) Inventors: KLOTS, Boris; 1566 Winding Way, Belmont, CA 94002 (US). BAMFORD, Roger; 2430 Hyde Street, San Francisco, CA 94109 (US). (74) Agents: HICKMAN, Brian, D. et al.; Hickman Palermo Truong & Becker, 1600 Willow Street, San Jose, CA 95125 (US).			(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Published Without international search report and to be republished upon receipt of that report.

(54) Title: COMMUNICATION ARCHITECTURE FOR DISTRIBUTED COMPUTING ENVIRONMENT

(57) Abstract

A communication architecture for performing work in a distributed computing environment involves client processes on client nodes sending work requests to a director. The director examines the work requests to determine one or more resources required to perform the work as well as one or more server nodes that can provide the required resources. The director then forwards the work requests to server processes on the server nodes that can provide the required resources. The work requests provided to the server processes specify that the work results are to be provided directly from the server processes to the client processes that made the work requests. The director maintains a table of resource data that specifies the services and/or resources that are provided by and/or made available on the server nodes in the distributed computing environment.



*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## COMMUNICATION ARCHITECTURE FOR DISTRIBUTED COMPUTING ENVIRONMENT

## FIELD OF THE INVENTION

5           The present invention relates to distributed computing, and more specifically, to a communication architecture for a distributed computing environment.

## BACKGROUND OF THE INVENTION

          In a distributed computing environment, work can be performed on multiple computing entities, often referred to as "nodes." In the context of distributed  
10   computing, the term "work" refers to any processing of data. One example of a node is a computer system on which one or more processes or threads may execute. Nodes in a distributed computing environment are typically communicatively coupled, for example via a network, to allow processes on nodes to access resources on other nodes. In a hardware context, a resource is generally a device such as a printer, disk  
15   drive or memory. In a software context, a resource is generally an item of data or a routine.

          An important concern in distributed computing is how to provide communication between processes on different nodes to ensure that work is completed in an orderly and efficient manner. Two such prior approaches include the  
20   direct communication architecture and the managed communication architecture.

## DIRECT COMMUNICATION ARCHITECTURE

          According to the direct communication architecture, processes communicate directly with processes on other nodes to request that work be performed and to obtain  
25   work results. FIG. 1 illustrates a distributed computing system 100 that uses a direct communication architecture approach. Distributed computing system 100 includes nodes N1-N5. Nodes N1 and N2 are each communicatively coupled to nodes N3-N5 via connections that provide for the exchange of data between nodes N1 and N2 and nodes N3-N5. Specifically, node N1 is connected to node N3 via connection 102, to

node N4 via connection 104 and to node N5 via connection 106. Node N2 is connected to node N3 via connection 108, to node N4 via connection 110 and to node N5 via connection 112.

A node having processes that require work to be performed is referred to herein as a "client" node. Processes on client nodes that require work to be performed are client processes. A node having processes that provide a service to and/or perform work on behalf of processes on other nodes is referred to herein as a "server" node. Processes on server nodes that provide a service and/or perform work on behalf of client processes are server processes. Sometimes nodes have both client processes and server processes executing thereon and therefore the "client node" and "server node" terminology is used herein to aid in understanding prior approaches and embodiments of the invention.

In distributed computing system 100, nodes N1 and N2 are client nodes while nodes N3-N5 are server nodes. When a particular client process on client node N1 requires work to be performed on server node N3, the particular client process sends a request directly to a server process on node N3 over connection 102. The request may be in any form, for example a remote procedure call (RPC). The process on server node N3 performs the requested work and provides the results directly to the particular client process. Work is similarly performed on server nodes N3-N5 on behalf of client processes on client node N2.

According to the direct communication architecture approach, client processes communicate directly with server processes that can perform work for the client processes. A disadvantage of this approach is that client processes must know which server process can perform the required work. When the services offered by any of the server processes change, the client nodes must be made aware of the change. Similarly, when a new service is provided, the client processes must be made aware of the new server node. The services offered by a server process can change when either the operations performed by the server process change or when the resources that a server process operates on change. For distributed computing systems with a large

number of client processes and server nodes, a significant amount of system resources can be required to keep all of the client processes updated.

### MANAGED COMMUNICATION ARCHITECTURE

5           According to the managed communication architecture approach, client processes send work requests to a management process referred to herein as a "director." The director forwards the work requests to the appropriate server process that can perform the required work. After performing the work, the server processes send the work results to the director, which forwards the work results to the client  
10   process that made the original work request.

FIG. 2 illustrates a distributed computing system 200 that uses a managed communication architecture approach. Distributed computing system 200 includes client nodes N1 and N2 and server nodes N3-N5. Client nodes N1 and N2 are each communicatively coupled to a director 202 via connections 204 and 206, respectively.  
15   Client processes on client nodes N1 and N2 submit work requests to director 202 via connections 204 and 206. Director 202 determines which of the server nodes N3-N5 can perform the requested work and forwards the work requests to the appropriate server process on server node N3-N5 on connections 208, 210 and 212, respectively. After the appropriate server process has performed the requested work, the server  
20   process provides the work results to director 202. Director 202 then forwards the work results to the client process that requested the work.

According to the managed communication architecture approach, director 202 keeps track of the services provided by server nodes N3-N5. As a result, when a change in services offered by server nodes N3-N5 occurs, only director 202 has to be  
25   informed and not client processes on client nodes N1 and N2. This reduces the amount of system resources required to keep track of changes in services offered by server nodes N3-N5, particularly when there are a large number of server nodes. However, the managed communication architecture approach requires more system resources than the direct communication architecture to manage the additional

messaging traffic associated with director 202. For example, for a single work request, the direct communication architecture approach requires two messages, one message from a client process to a server process and one message from the server process back to the client process. To process the same work request, the managed communication architecture requires four messages, one from the client process to the director, one from the director to the server process, one from the server process back to the director and one from the director back to the client process.

Based on the need to perform work in a distributed computing environment and the limitations in the prior communication architectures, a communication architecture for a distributed computing environment that avoids the limitations in the approaches previously described is highly desirable.

#### SUMMARY OF THE INVENTION

According to one aspect of the invention, a method is provided for processing data on a distributed computing system that includes a plurality of nodes. The method comprises the steps of, in response to receiving a first work request to perform first work from a first process on a first node, determining based upon the first work that the first work is to be performed on a second node and providing the first work request to a second process on the second node. The first work request specifies that the first process is to receive results of the first work directly from the second process.

According to another aspect of the invention, a method is provided for processing data on a distributed computing system that includes a plurality of nodes. A director receives a first remote procedure call from a first client process on a first client node. The first remote procedure call requests that first work be performed and that results of the first work be provided directly to the first client process. The director examines the first remote procedure call and determines that a first server process on a first server node is to perform the first work. Then the director provides the first remote procedure call to the first server process.

According to another aspect of the invention, a distributed computing system for performing work comprises a plurality of nodes and a director communicatively coupled to the plurality of nodes. The director is configured to, in response to a first work request to perform first work from a first process on a first node, determine that  
5 the first work is to be performed on a second node from the plurality of nodes. The director is further configured to request that the first work be performed by a second process on the second node and that first results of the first work be provided from the second process directly to the first process.

## 10 BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the invention are illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings and in which like reference numerals refer to similar elements and in which:

FIG. 1 is a block diagram illustrating a conventional distributed computing  
15 system that uses a direct communication architecture to perform work;

FIG. 2 is a block diagram illustrating a conventional distributed computing system that uses a managed communication architecture to perform work;

FIG. 3 is a block diagram illustrating a distributed computing system using a communication architecture to perform work according to an embodiment of the  
20 invention;

FIG. 4 is a flow chart illustrating an approach for performing work in a distributed computing system according to an embodiment of the invention;

FIG. 5 is a resource data table according to an embodiment of the invention;  
and

25 FIG. 6 is a block diagram of a computer system on which embodiments of the invention may be implemented.

## DETAILED DESCRIPTION OF THE INVENTION

In the following description, for the purposes of explanation, specific details are set forth in order to provide a thorough understanding of the invention. However, it will be apparent that the invention may be practiced without these specific details.

- 5 In other instances, well-known structures and devices are depicted in block diagram form in order to avoid unnecessarily obscuring the invention.

## FUNCTIONAL OVERVIEW

- In general, the communication architecture for performing work in a distributed computing environment, according to an embodiment of the invention,
- 10 involves client processes on client nodes sending work requests to a director. The director examines the work requests to determine resources and/or services that are required to perform the requested work. The director then forwards the work requests to server processes on server nodes that can perform the requested work. The work requests provided to the server processes specify that work results are to be provided
- 15 directly from the server processes to the client processes that made the work requests. Consequently, server processes provide their work results directly to the client processes that requested the work, thereby bypassing the director. This approach eliminates the need for client processes to be aware of the services provided by the server processes and nodes while requiring relatively fewer system resources than
- 20 conventional managed communication architectures.

## DETAILED DESCRIPTION

- FIG. 3 illustrates a distributed computing system 300 that uses a communication architecture for performing work according to an embodiment of the invention. Distributed computing system 300 includes client nodes N1 and N2 and
- 25 server nodes N3-N5. Client nodes N1 and N2 are each communicatively coupled to a director 302 via connections 304 and 306, respectively. Client processes on client nodes N1 and N2 submit work requests to director 302 via connections 304 and 306. Director 302 determines which of the server nodes N3-N5 can perform the requested



work and forwards the work requests to a server process on one or more of server nodes N3-N5 on connections 308, 310 and 312, respectively. Director 302 then forwards the work request to the particular server process. The work requests specify where the results of performing the requested work are to be sent, i.e. to client node

5 N1 or N2. Director 302 is described in more detail hereinafter.

After the server processes on server nodes N3-N5 have performed the requested work, server nodes N3-N5 provide the work results directly to the client processes on client nodes N1 and N2 that made the work request, bypassing director 302. Specifically, server processes on server node N3 provide work results to client

10 processes on client nodes N1 and N2 via connections 314 and 316, respectively. Server processes on server node N4 provide work results to client processes on client nodes N1 and N2 via connections 318 and 320, respectively. Server processes on server node N5 provide work results to client processes on client nodes N1 and N2 via connections 322 and 324, respectively.

15 The approach for performing work on a distributed computing system is now described with reference to both the block diagram of FIG. 3 and the flow chart 400 of FIG. 4. Referring to FIG. 4, after starting in step 402, in step 404 a requestor, e.g. a client process on client node N1, sends a work request to director 302 over connection 304 or 306. In step 406, director 302 examines the work request and determines

20 which of the server nodes N3-N5 can perform the requested work. According to one embodiment of the invention, director 302 examines the work request to identify the service required to perform the requested work, where a service is a particular operation on a particular resource. Director 302 then compares the required service to services supported by server nodes N3-N5 to determine which server node N3-N5 can

25 provide the required service.

According to another embodiment of the invention, director 302 determines which of the server nodes N3-N5 can provide the required service by determining the particular server process on server nodes N3-N5 that holds the exclusive rights (i.e. a lock) to a resource required by the service.

In step 408, director 302 sends the work request to a server process on one or more of server nodes N3-N5 that can perform the requested work. The work request sent to the server process on one or more of server nodes N3-N5 specifies that the work results are to be sent directly to the client process on client node N1 or N2 that requested the work be performed.

For example, suppose a client process on client node N1 sends a particular work request to perform particular work to director 302 over connection 304. Director 302 examines the particular work request and determines that a server process on server node N3 can perform the particular work. Director 302 forwards the particular work request to the server process on server node N3. The particular work request sent to the to the server process on server nodes N3 specifies that the results of the particular work are to be sent to the client process on client node N1.

The particular work request sent by the client process on client node N1 may specify that the client process on client node N1 is to receive the results of the particular work. According to another embodiment of the invention, the particular work request from client node N1 does not specify that client node N1 is to receive the results of the particular work. In this situation, director 302 determines where the work request originated, i.e. client node N1, and generates a new particular work request that specifies where the results of the particular work are to be sent, i.e. the client process on client node N1.

In situations where the requested work requires resources on more than one server node, a work request is sent to a server process on each server node where work is to be performed. Each work request specifies the client node where the work results are to be sent. For example, suppose for the particular work request from client node N1 that director 302 determines that both server nodes N3 and N4 are required to perform the particular work. Director 302 provides a work request to server processes on both server node N3 and N4. Both work requests specify that the client process on client node N1 is to receive the results of the particular work.

In step 410 the work is performed at the server nodes N3-N5 that received the work request. In step 412, the work results are provided from the server processes on server nodes N3-N5 that performed the work directly to the client process on client node N1 or N2 that requested the work on connection 314, 316, 318, 320, 322 or 324.

5 For example, if a client process on client node N1 had requested the work and director 302 sent the work request to server process on server node N3, then the server process on server node N3 provides the work results to a client process on client node N1 on connection 314. If the work request was sent to a server process on server nodes N4 and N5, then the work results are provided to client node N1 on connections 318 and

10 322, respectively. The process is complete in step 414.

### THE DIRECTOR

Director 302 may be implemented on one or more client nodes N1 and N2, server nodes N3-N5, or one or more other nodes (not illustrated) in distributed

15 computing system 300. More than one director may be used in a distributed computing system. For example, in a distributed computing system having a large number of client nodes, using several directors can improve system performance by reducing the number of work requests that are processed by a single director. For example, in a distributed computing system having thirty (30) client nodes and five

20 (5) server nodes, three (3) directors may be used. Each director services ten (10) client nodes and provides work requests to all five (5) server nodes.

As previously described, director 302 keeps track of the services provided by server process executing on server nodes N3-N5 so that work requests can be forwarded to the correct server node N3-N5. According to one embodiment of the

25 invention, director 302 maintains the global state of server nodes N3-N5 and the server processes executing thereon. Then director 302 implements logic to determine which server process holds the exclusive rights to a resource required to process a work request.

FIG. 5 is a table 500 of resource data maintained by director 302 according to an embodiment of the invention. Table 500 includes entries 502, 504 and 506 for each server node N3-N5 in distributed computing system 300. Each entry 502, 504 and 506 specifies the server node that the entry 502, 504 and 506 is associated with (SERVER NODE ID) and data that specifies the services and/or resources provided by and/or available on the associated server node (SERVER NODE SERVICE DATA). For example, entry 502 is associated with server node N3 and contains data (DATA1) that specifies the services provided by server node N3.

Any change in services provided by server nodes N3-N5 is reflected in table 500. In addition, if a new server node (not illustrated) is added to distributed computing system 300, then a new entry is added to table 500 for the new server node. Similarly, if a server node N3-N5 is removed from distributed computing system 300, then the entry 502, 504, 506 associated with the removed server node N3-N5 is removed from table 500.

## IMPLEMENTATION MECHANISMS

The communication architecture for performing work in a distributing computing system as described herein may be implemented in discrete hardware circuitry, in computer software, or a combination of discrete hardware circuitry and computer software. The communication architecture described herein in accordance with the present invention is not limited to a particular type of messaging protocol. For example, node-to-node communication may be implemented with remote procedure calls (RPCs) or any other messaging protocol for requesting that work be performed on a remote node.

FIG. 6 is a block diagram that illustrates a computer system 600 upon which an embodiment of the invention may be implemented. Computer system 600 includes a bus 602 or other communication mechanism for communicating information, and a processor 604 coupled with bus 602 for processing information. Computer system 600 also includes a main memory 606, such as a random access memory (RAM) or other

dynamic storage device, coupled to bus 602 for storing information and instructions to be executed by processor 604. Main memory 606 also may be used for storing temporary variables or other intermediate information during execution of instructions to be executed by processor 604. Computer system 600 further includes a read only  
5 memory (ROM) 608 or other static storage device coupled to bus 602 for storing static information and instructions for processor 604. A storage device 610, such as a magnetic disk or optical disk, is provided and coupled to bus 602 for storing information and instructions.

Computer system 600 may be coupled via bus 602 to a display 612, such as a  
10 cathode ray tube (CRT), for displaying information to a computer user. An input device 614, including alphanumeric and other keys, is coupled to bus 602 for communicating information and command selections to processor 604. Another type of user input device is cursor control 616, such as a mouse, a trackball, or cursor direction keys for communicating direction information and command selections to processor 604 and for  
15 controlling cursor movement on display 612. This input device typically has two degrees of freedom in two axes, a first axis (e.g., x) and a second axis (e.g., y), that allows the device to specify positions in a plane.

The invention is related to the use of computer system 600 for implementing a communication architecture for a distributed computing system. According to one  
20 embodiment of the invention, a communication architecture for a distributed computing system is provided by computer system 600 in response to processor 604 executing one or more sequences of one or more instructions contained in main memory 606. Such instructions may be read into main memory 606 from another computer-readable medium, such as storage device 610. Execution of the sequences  
25 of instructions contained in main memory 606 causes processor 604 to perform the process steps described herein. One or more processors in a multi-processing arrangement may also be employed to execute the sequences of instructions contained in main memory 606. In alternative embodiments, hard-wired circuitry may be used in place of or in combination with software instructions to implement the invention.

Thus, embodiments of the invention are not limited to any specific combination of hardware circuitry and software.

The term "computer-readable medium" as used herein refers to any medium that participates in providing instructions to processor 604 for execution. Such a medium  
5 may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. Non-volatile media includes, for example, optical or magnetic disks, such as storage device 610. Volatile media includes dynamic memory, such as main memory 606. Transmission media includes coaxial cables, copper wire and fiber optics, including the wires that comprise bus 602. Transmission media can also take the  
10 form of acoustic or light waves, such as those generated during radio wave and infrared data communications.

Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, a CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium  
15 with patterns of holes, a RAM, a PROM, and EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read.

Various forms of computer readable media may be involved in carrying one or more sequences of one or more instructions to processor 604 for execution. For  
20 example, the instructions may initially be carried on a magnetic disk of a remote computer. The remote computer can load the instructions into its dynamic memory and send the instructions over a telephone line using a modem. A modem local to computer system 600 can receive the data on the telephone line and use an infrared transmitter to convert the data to an infrared signal. An infrared detector coupled to bus 602 can  
25 receive the data carried in the infrared signal and place the data on bus 602. Bus 602 carries the data to main memory 606, from which processor 604 retrieves and executes the instructions. The instructions received by main memory 606 may optionally be stored on storage device 610 either before or after execution by processor 604.

Computer system 600 also includes a communication interface 618 coupled to bus 602. Communication interface 618 provides a two-way data communication coupling to a network link 620 that is connected to a local network 622. For example, communication interface 618 may be an integrated services digital network (ISDN) card or a modem to provide a data communication connection to a corresponding type of telephone line. As another example, communication interface 618 may be a local area network (LAN) card to provide a data communication connection to a compatible LAN. Wireless links may also be implemented. In any such implementation, communication interface 618 sends and receives electrical, electromagnetic or optical signals that carry digital data streams representing various types of information.

Network link 620 typically provides data communication through one or more networks to other data devices. For example, network link 620 may provide a connection through local network 622 to a host computer 624 or to data equipment operated by an Internet Service Provider (ISP) 626. ISP 626 in turn provides data communication services through the world wide packet data communication network now commonly referred to as the "Internet" 628. Local network 622 and Internet 628 both use electrical, electromagnetic or optical signals that carry digital data streams. The signals through the various networks and the signals on network link 620 and through communication interface 618, which carry the digital data to and from computer system 600, are exemplary forms of carrier waves transporting the information.

Computer system 600 can send messages and receive data, including program code, through the network(s), network link 620 and communication interface 618. In the Internet example, a server 630 might transmit a requested code for an application program through Internet 628, ISP 626, local network 622 and communication interface 618. In accordance with the invention, one such downloaded application provides for implementation of a communication architecture for a distributed computing system as described herein.

The received code may be executed by processor 604 as it is received, and/or stored in storage device 610, or other non-volatile storage for later execution. In this manner, computer system 600 may obtain application code in the form of a carrier wave.

5           The communication architecture described herein provides several advantages over prior communication architectures for distributed computing environments. First, the use of a director to forward work requests to server nodes eliminates the need for client nodes to know what services are provided by client nodes. As a result, client nodes do not have to be made aware of changes in the services offered by server  
10       nodes. In addition, the approach requires fewer message transfers to perform work and provide work results to a client process than the managed communication architecture approach since work results are provided by server nodes directly to client nodes. For example, to process a work request, embodiments of the present invention require three messages instead of four messages as required by managed  
15       communication architecture approaches. Specifically, the three messages include one from a client process to the director, one from the director to a server process and one from the server process back to the client process.

          In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various  
20       modifications and changes may be made thereto without departing from the broader, spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.



## CLAIMS

What is claimed is:

- 1 1. A method for processing data on a distributed computing system that includes  
2 a plurality of nodes, the method comprising the steps of:  
3 in response to receiving a first work request to perform first work from a first  
4 process on a first node from the plurality of nodes, determining based  
5 upon the first work that the first work is to be performed on a second  
6 node from the plurality of nodes; and  
7 providing the first work request to a second process on the second node,  
8 wherein the first work request specifies that the first process is to  
9 receive results of the first work directly from the second process.
- 1 2. The method as recited in Claim 1, further including the steps of  
2 in response to receiving a second request to perform second work from the  
3 first process, determining that the second work is to be performed on a  
4 third node from the plurality of nodes, and  
5 providing the second request to a third process on the third node, wherein the  
6 second request specifies that the first process is to receive results of the  
7 second work directly from the third process.
- 1 3. The method as recited in Claim 1, further including the steps of  
2 in response to receiving a second request to perform second work from a third  
3 process on a third node from the plurality of nodes, determining that  
4 the second work is to be performed on the second node, and  
5 providing the second request to the second process, wherein the second  
6 request specifies that the third process is to receive results of the  
7 second work directly from the second process.

- 1    4.    The method as recited in Claim 1, further including the steps of  
2            in response to receiving a second request to perform second work from a third  
3            process on a third node from the plurality of nodes, determining a  
4            fourth node from the plurality of nodes on which the second work is to  
5            be performed, and  
6            providing the second request to a fourth process on the fourth node, wherein  
7            the second request specifies that the third process is to receive results  
8            of the second work directly from the fourth process.
- 1    5.    The method as recited in Claim 1, further including the steps of  
2            determining that the first work is also to be performed on a third node from the  
3            plurality of nodes, and  
4            providing a second request to a third process on the third node, wherein the  
5            second request specifies that results of the first work performed on the  
6            third node are to be provided from the third node directly to the first  
7            process.
- 1    6.    The method as recited in Claim 1, wherein the step of determining that the  
2            first work is to be performed on a second node includes the step of  
3            determining one or more resources required to perform the first work, and  
4            determining which of the plurality of nodes is allowed to perform the first  
5            work on the one or more resources.
- 1    7.    The method as recited in Claim 1, wherein:  
2            the step of determining that the first work is to be performed on a second node  
3            from the plurality of nodes includes the step of a director determining  
4            that the first work is to be performed on a second node from the  
5            plurality of nodes, and  
6            the step of providing the first work request to a second process on the second  
7            node includes the step of the director providing the first work request  
8            to a second process on the second node.

- 1 8. The method as recited in Claim 1, further comprising the step of upon  
2 completion of the first work, the second process providing the results of the  
3 first work directly to the first process.
- 1 9. The method as recited in Claim 1, wherein the first work request is a remote  
2 procedure call.
- 1 10. The method as recited in Claim 1, further including the step of generating an  
2 updated first work request that specifies that the first process is to receive the  
3 first results of performing the first work and wherein the step of providing the  
4 first work request to a second process includes the step of providing the  
5 updated first work request to the second process.
- 1 11. A method for processing data on a distributed computing system that includes  
2 a plurality of nodes, the method comprising the steps of:  
3 a director receiving a first remote procedure call from a first client process on  
4 a first client node from the plurality of nodes, wherein the first remote  
5 procedure call requests that first work be performed and that results of  
6 the first work be provided directly to the first client process;  
7 the director examining the first remote procedure call and determining that a  
8 first server process on a first server node from the plurality of nodes is  
9 to perform the first work; and  
10 the director providing the first remote procedure call to the first server process.
- 1 12. The method as recited in Claim 11, further including the steps of  
2 the director determining one or more resources required to perform the first  
3 work, and  
4 the director determining which of the plurality of nodes have permission to  
5 perform a requested operation on the one or more resources required to  
6 perform the first work.

- 1 13. The method as recited in Claim 12, wherein the step of the director  
2 determining the resources available on the plurality of nodes includes the  
3 director examining resource data associated with the plurality of nodes.
- 1 14. The method as recited in Claim 11, further including the steps of  
2 the director receiving a second remote procedure call from the first client  
3 process, wherein the second remote procedure call requests that second  
4 work be performed and that results of the second work be provided  
5 directly to the first client process,  
6 the director examining the second remote procedure call and determining that  
7 a second server process on a second server node from the plurality of  
8 nodes is to perform the second work, and  
9 the director providing the second remote procedure call to the second server  
10 process.
- 1 15. The method as recited in Claim 11, further including the steps of  
2 the director receiving a second remote procedure call from a second client  
3 process on a second client node in the plurality of nodes, wherein the  
4 second remote procedure call requests that second work be performed  
5 and that results of the second work be provided directly to the second  
6 client process,  
7 the director examining the second remote procedure call and determining that  
8 a second server process on a second server node from the plurality of  
9 nodes is to perform the second work, and  
10 the director providing the second remote procedure call to the second server  
11 process.
- 1 16. A distributed computing system for performing work, the distributed  
2 computing system comprising:  
3 a plurality of nodes; and

4 a director communicatively coupled to the plurality of nodes, the director  
5 being configured to  
6 in response to a first work request to perform first work from a first  
7 process on a first node from the plurality of nodes, determine  
8 that the first work is to be performed on a second node from the  
9 plurality of nodes, and  
10 request that the first work be performed by a second process on the  
11 second node, wherein the request specifies that first results of  
12 the first work be provided from the second process directly to  
13 the first process.

1 17. The distributed computing system as recited in Claim 16, wherein the director  
2 is further configured to provide the first work request to the second process.

1 18. The distributed computing system as recited in Claim 16, wherein the director  
2 is further configured to  
3 generate a second work request to requests that the second process perform the  
4 first work and provide the first results directly to the first process, and  
5 provide the second work request to the second process.

1 19. The distributed computing system as recited in Claim 16, further comprising  
2 resource data that specifies the access rights of the plurality of nodes relative  
3 to resources.

1 20. A computer-readable medium carrying one or more sequences of one or more  
2 instructions for processing data on a distributed computing system that  
3 includes a plurality of nodes, the one or more sequences of one or more  
4 instructions include instructions which, when executed by one or more  
5 processors, cause the one or more processors to perform the steps of:  
6 in response to receiving a first work request to perform first work from a first  
7 process on a first node from the plurality of nodes, determining based

8                   upon the first work that the first work is to be performed on a second  
9                   node from the plurality of nodes; and  
10                  providing the first work request to a second process on the second node,  
11                   wherein the first work request specifies that the first process is to  
12                   receive results of the first work directly from the second process.

1   21.   The computer-readable medium as recited in Claim 20, further including the  
2           steps of  
3           in response to receiving a second request to perform second work from the  
4                   first process, determining that the second work is to be performed on a  
5                   third node from the plurality of nodes, and  
6           providing the second request to a third process on the third node, wherein the  
7                   second request specifies that the first process is to receive results of the  
8                   second work directly from the third process.

1   22.   The computer-readable medium as recited in Claim 20, further including the  
2           steps of  
3           in response to receiving a second request to perform second work from a third  
4                   process on a third node from the plurality of nodes, determining that  
5                   the second work is to be performed on the second node, and  
6           providing the second request to the second process, wherein the second  
7                   request specifies that the third process is to receive results of the  
8                   second work directly from the second process.

1   23.   The computer-readable medium as recited in Claim 20, further including the  
2           steps of  
3           in response to receiving a second request to perform second work from a third  
4                   process on a third node from the plurality of nodes, determining a  
5                   fourth node from the plurality of nodes on which the second work is to  
6                   be performed, and

7 providing the second request to a fourth process on the fourth node, wherein  
8 the second request specifies that the third process is to receive results  
9 of the second work directly from the fourth process.

1 24. The computer-readable medium as recited in Claim 20, further including the  
2 steps of  
3 determining that the first work is also to be performed on a third node from the  
4 plurality of nodes, and  
5 providing a second request to a third process on the third node, wherein the  
6 second request specifies that results of the first work performed on the  
7 third node are to be provided from the third node directly to the first  
8 process.



1 25. The computer-readable medium as recited in Claim 20, wherein the step of  
2 determining that the first work is to be performed on a second node includes  
3 the step of  
4 determining one or more resources required to perform the first work, and  
5 determining which of the plurality of nodes is allowed to perform the first  
6 work on the one or more resources.

1 26. The computer-readable medium as recited in Claim 20, wherein:  
2 the step of determining that the first work is to be performed on a second node  
3 from the plurality of nodes includes the step of a director determining  
4 that the first work is to be performed on a second node from the  
5 plurality of nodes, and  
6 the step of providing the first work request to a second process on the second  
7 node includes the step of the director providing the first work request  
8 to a second process on the second node.


- 1 27. The computer-readable medium as recited in Claim 20, further comprising the  
2 step of upon completion of the first work, the second process providing the  
3 results of the first work directly to the first process.
- 1 28. The computer-readable medium as recited in Claim 20, wherein the first work  
2 request is a remote procedure call.
- 1 29. The computer-readable medium as recited in Claim 20, further including the  
2 step of generating an updated first work request that specifies that the first  
3 process is to receive the first results of performing the first work and wherein  
4 the step of providing the first work request to a second process includes the  
5 step of providing the updated first work request to the second process.




1/5

*Fig. 1 (Prior Art)**Fig. 2 (Prior Art)*

2/5

*Fig. 3*

3/5

*Fig. 4*

4/5

500  
↓

RESOURCE DATA

	SERVER NODE ID	SERVER NODE SERVICE DATA
502 →	N3	DATA1
504 →	N4	DATA2
506 →	N5	DATA3

*Fig. 5*




Fig. 6